

Data sheet

040C2325-1E

Aluminium push-button enclosure M4 230x257x100, undrilled, with cable entry



Features

Range	040 Metal Push-Button Enclosures and Boxes
Product	Aluminium push-button enclosures M4 230x257 mm
Type	Undrilled lid
Item code	040C2325-1E
Description	Aluminium push-button enclosure M4 230x257x100, undrilled, with cable entry
Colour	Grey RAL7035
Weight - gr	2180,000
Custom tariff no.	85381000
GTIN	8052878046439

Technical data

Approvals	CE, UL, CSA
Compliance with standards	IEC-60529, UL508A, UL50, UL50E, CSA C22.2 No.14-13
Operating temperatures	-40° ÷ +100°C
Protection degree	IP66 - IP69K - TYPE 4, 4X (IEC-EN60529 - NEMA 250)
Protection against impact	IK09 (IEC-EN62262)
Manufacturing process	Shell gravity diecasting
Enclosure material	Aluminum Al Si12 Cu (EN AC47000)
Gasket material	Cork rubber
Screw material	Stainless steel AISI 304
Tightening torque	2,5Nm (22.1 Lb-in)
Overvoltage category	Class I (IEC-EN61140)
Warranty period	18 months

Data sheet

040C2325-1E

Aluminium push-button enclosure M4 230x257x100,
undrilled, with cable entry

Technical drawings

